

## Application

- Suitable for external use, allows for non-structural infill, ideal in paved environments.
- Ideal where easy access to underground cabling is required.
- Designed to blend in aesthetically with the surrounding area.

## Technical Description

- Manufactured from high grade 6 mm mild steel
- Hot-dip galvanized 70µm minimum coating according to ISO1461
- Cover sides tapered to facilitate easy removal of cover from frame
- DDA compliant.
- One person operation when using **SOLO SLIDE®** key
- Bolt fixing provision to ensure maximum performance
- Manufactured in accordance with BT LN593 specification
- BSI Kitemark™ Approval No. KM 6405
- Tested unfilled to A15 & B125
- For comparisons to FACTA, see our [FACTA v EN124 FAQ](#)

## Options

- Depths from 70mm to 150mm in tray
- Hot-dip galvanized coating 100µm or 140µm
- Stainless steel (304 or 316)
- Locking
- Badging Identification marking

### Accessories

- Solo Slide® lifting key (COM0000563)
- DDA compliant protective keyway cap (COM00000651)
- RESI-Bed Epoxy Resin (COM0001366)
- Fixing Bolt (COM0000309)

## Opening Dimensions

- Standard clear openings include:
 

725x255mm	1310x610mm
610x610mm	1690x710mm
915x445mm	2285x710mm
- *Bespoke sizes available upon request*
- 250x250mm to a maximum span of 1000mm (e.g. 3500x1000mm)

