

## Application

- Suitable for external use, allows for non-structural infill, ideal in paved environments.
- Typical applications are retail parks and public areas of high prestige.
- Designed to blend in aesthetically with the surrounding area.

## Technical Description

- Manufactured from Grade S275J2 Mild Steel
- Hot-dip galvanized 70µm minimum coating according to ISO1461
- Robust keyways to accept industry standard lifting keys with no unsightly welds
- Cover sides tapered to facilitate easy removal of cover from frame
- Bolt fixing provision to ensure maximum performance
- **Available in FACTA loadings:**



- For more info, see our [FACTA FAQ](#)

## Options

- Depths from 60mm to 150mm in tray (loading dependent)
- Hot-dip galvanized coating 100µm or 140µm
- Stainless steel (304 or 316)
- Identification marking

## Accessories

- Looped handled lifting key (COM0000048)
- Protective keyway cap (COM00000182)
- RESI-Bed Epoxy Resin (COM0001366)
- Fixing Bolt (COM0000309)

## Opening Dimensions

- Standard clear openings include:
 

300x300mm	750x600mm
450x450mm	750x750mm
600x450mm	900x600mm
600x600mm	1200x600mm
675x675mm	1220x675mm
- Bespoke sizes available upon request
- 250x250mm to a maximum span of 1000mm (e.g. 3500x1000mm)
- 1 Part and 2 Part covers as standard. Duct runs for larger sizes

